



AX3 LightDrop™

Data sheet

Optical

Colours
RGBW
Total LED power
15W
Luminous Flux
390Lm
Emittance (@2m)
1300Lx
Strobe
0-25Hz
Beam Angle
13 °
Pixels
1

Electrical

Battery
LG Chem Lithium-ion
Battery Lifetime
70% after 300 cycles
Battery Runtime
Up to 20 hours
LED Lifetime
50.000 Hours
Charging time (nominal)
7 Hours
Input Voltage (charger)
90-264V 47-63Hz
Input voltage (light)
5V 2.5A

Control

Wireless Modules
865-870MHz
902-928MHz
2.4GHz
Range
300m | 330 Yards
DMX
Supports CRMX and W-DMX

Construction

Housing
ABS
IP Rating
IP65
Relative humidity
0-100%
Operating Temperature
0-40 °C
32-104 °F
Weight
0.679kg
1.4Lbs
Dimensions (with bracket)
120 x 59 x 114 (mm)
7.4 x 2.3 x 4.4 (inches)

Accessories



Charger
AX3-CHR (Included)



Hooks (3)
AX3-EBLT (Included)



Rubber Feet (4)
AX3-FEET (Included)



Bracket
AX3-STA (Included)



30° diffuser
AX3-DDSK30 (Included)



120° diffuser
AX3-DDSK-120 (Included)



Wallwash diffuser
AX3-WWDSK



Diffuser dome
AX3-DDM



Charging case
AX3-CHRCSE



Clamp
AX3-CLP

