



# AX7 SpotLite™

## Data sheet

## Optical

Colours  
RGBW  
Total LED power  
60W  
Luminous Flux  
1675Lm  
Emittance (@2m)  
6250Lx  
Strobe  
0-25Hz  
Beam Angle  
13 °  
Pixels  
1

## Construction

Housing  
Aluminium  
IP Rating  
IP65  
Relative humidity  
0-100%  
Operating Temperature  
0-40 °C  
32-104 °F  
Weight  
6.1kg  
13.4Lbs  
Dimensions  
279 x 296 x 253 (mm)  
10.9 x 11.6 x 9.9 (inches)

## Accessories



Powercon True1 cord  
AX10-CHR (Included)



32° Flood diffusor  
AX10-DDSK (Included)



13°x 46° Wallwash diffusor  
AX10-WWDSK (Included)



13°x 46° Rotatable diffusor  
AX10-ROTAD



Charging case  
AX10-CHRCSE



Super bolt  
AX10-BLT

## Electrical

Battery  
LG Chem Lithium-ion  
Battery Lifetime  
70% after 300 cycles  
LED Lifetime  
50.000 Hours  
Charging time (nominal)  
7 Hours  
Input Voltage  
90-264V 47-63Hz  
Input Current  
1.8A/115VAC ~ 1.0A/230VAC  
Inrush Current  
Cold start 60A/230VAC

## Control

Wireless Modules  
865-870MHz  
902-928MHz  
2.4GHz  
Range  
300m | 330 Yards  
DMX  
Supports CRMx and W-DMX

